Data sheet

17023.2 HSKG 120/M10/B/B BG



High-power stud terminal, Stud connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 120 mm², Width: 42 mm, Colour: Beige

Business data

Article number	17023.2
Article name	HSKG 120/M10/B/B BG
GTIN (EAN)	4044211177416
Packaging unit	5
Quantity unit	PC
Weight per piece (not including packaging)	230 g
Weight per piece (including packaging)	245.7 g
Unit of weight	G
Customs number	85369010
Country of origin	DE
Product description	High-power stud terminal
Colour	Beige

Data sheet

17023.2 HSKG 120/M10/B/B BG

Technical data

Dimensions

Length	133 mm
Length with TW/ADH	226 mm
Width	42 mm
Height TS 35/7.5	72 mm
Height TS 35/7.5 with TW/ADH	80 mm

Ratings

Rated voltage	1000 V
Rated current	269 A
Rated cross-section	120 mm²
Rated impulse voltage	8 kV
Overvoltage category	III
Contamination degree	3
Maximum power dissipation for nominal condition	8.61 W

Connection data

Connection principle	Stud connection
Connection position	Top
Connections	2
Number of terminals per level	2
Number of levels	1
Wire cross-section AWG, min.	10
Wire cross-section AWG, max.	250 Kcmil
Bolt head	Hexagon
Bolt thread	M 10
Tightening torque, min.	10 Nm
Tightening torque, max.	20 Nm
Contact wire range	≤ 120 mm²

Materials

Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	120 °C

Data sheet

17023.2 HSKG 120/M10/B/B BG

Technical data

Further technical data

Mounting type	Mounting rail TS 35/7,5
Spanner width (AF)	17 mm
Number of cross-connection channels	2
DIN 46234 / 1 cable lug per side, min.	6 mm²
DIN 46234 / 1 cable lug per side, max.	15 mm²
DIN 46234 / 2 cable lugs per side, min.	6 mm²
DIN 46234 / 2 cable lugs per side, max.	120 mm²
DIN 46235: 1 cable lug per side, max.	150 mm²
DIN 46235: 1 cable lug per side, min.	16 mm²
DIN 46235: 2 cable lugs per side, min.	16 mm²
DIN 46235: 2 cable lugs per side, max.	120 mm²

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet

17023.2 HSKG 120/M10/B/B BG

Approvals

Standards and regulations	
Bureau Veritas approval	IEC 60947-7-1
Bureau Veritas approval granted	yes
EAC approval	TR ZU 004/2011
EAC approval granted	yes

cUL Recognized	
cUL approval	C22.2 No 158
cUL Usegroup B: rated voltage	1000 V
cUL Usegroup B: rated current	310 A
cUL Usegroup C: rated voltage	1000 V
cUL Usegroup C: rated current	310 A
cUL wire cross-section AWG, min.	10
cUL wire cross-section AWG, max.	250 Kcmil
cUL torque, min.	10 Nm
cUL torque, max.	20 Nm
cUL wire material	Cu
cUL Recognized	1

KEMA KEUR approval	
KEMA KEUR approval	EN 60947-7-1:2009
KEMA KEUR approval granted	yes
KEMA rated voltage	1000 V
KEMA rated current	269 A
KEMA rated impulse voltage	8 kV
KEMA wire cross-section, max.	120 mm²
KEMA torque, min.	10 Nm
KEMA torque, max.	20 Nm

Data sheet

17023.2 HSKG 120/M10/B/B BG

Approvals

UL Recognized

UL approval	UL 1059
UL Usegroup B: rated voltage	1000 V
UL Usegroup B: rated current (only for factory wiring)	225 (310) A
UL Usegroup C: rated voltage	1000 V
UL Usegroup C: rated current (only for factory wiring)	225 (310) A
UL wire cross-section AWG, min.	10
UL wire cross-section AWG, max.	250 Kcmil
UL torque, min.	88.5 Lb In.
UL torque, max.	177 Lb In.
UL wire material	Cu
UL factory wiring	1
UL field wiring	1
UL Recognized	1

German Lloyd approval

DNV GL Certificate number	TAE00002JH
DNV GL Location Classes	Temperature: B, Humidity: B, Vibration: A
DNV GL approval granted	1
DNV GL rated cross-section	120 mm²
DNV GL rated current	269 A
DNV GL rated impulse voltage	8 kV
DNV GL rated voltage	1000 V
DNV GL test standard	IEC 60947-7-1:2009

Data sheet

17023.2 HSKG 120/M10/B/B BG

Media



Accessories

Protective hood

Cover profile, Length: 110.2 mm, Width: 41.9 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17025.2	ADH 120 BG	4044211131685	10

End stop



End stop, Mounting type: Mounting rail TS 35/7.5, Width: 9.5 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2828.0	ES 35/K/ST BG	4044211055547	50

Cross-connection rail

Cross-connector, No. of poles: 2, Mounting type: Can be screwed on, Width: 77 mm, Rated cross-section: 120 mm², Colour: natural

Article number	Article name	GTIN (EAN)	Packaging unit
17241.0	QS 2/120/10	4044211178024	10 ST

Cross-connector, No. of poles: 3, Mounting type: Can be screwed on, Width: 119 mm, Rated cross-section: 120 mm², Colour: natural

Article number	Article name	GTIN (EAN)	Packaging unit
17242.0	QS 3/120/10	4044211178031	10 ST

Data sheet

17023.2 HSKG 120/M10/B/B BG

Quick marking



Terminal marker / Pocket Maxicard, Length: 5 mm, Width: 6 mm, Colour: White

Article number	Article name	GTIN (EAN)	Packaging unit
4702.7	PMC SB 6/50 WH	4044211089986	500 ST