



Insulated cross-connector, No. of poles: 8, Mounting type: Plug in, Width: 47.9 mm, Rated cross-section: 4 mm<sup>2</sup>, Colour: Red

### **Business data**

| Article number                             | <u>17217.9</u>            |
|--|---------------------------|
| Article name                               | SQI 4/8 RD                |
| GTIN (EAN)                                 | 4044211175337             |
| Packaging unit                             | 10                        |
| Quantity unit                              | PC                        |
| Weight per piece (not including packaging) | 6 g                       |
| Weight per piece (including packaging)     | 6.1 g                     |
| Unit of weight                             | G                         |
| Customs number                             | 85389099                  |
| Country of origin                          | DE                        |
| Prio-Article                               | 17217.8                   |
| Product description                        | Insulated cross-connector |
|  |                           |



### **Technical data**

| Dimensions                       |                   |
|----------------------------------|-------------------|
| Length                           | 4 mm              |
| Width                            | 47.9 mm           |
| Height                           | 23 mm             |
| Pitch size                       | 6 mm              |
| Ratings                          |                   |
| Voltage with partition, max.     | 1000 V            |
| Voltage without partition, max.  | 1000 V            |
| Rated current                    | 32 A              |
| Current load, max.               | 41 A              |
| Rated cross-section              | 4 mm <sup>2</sup> |
| Contamination degree             | 2                 |
| Connection data                  |                   |
| No. of poles                     | 8                 |
| Materials                        |                   |
| Material                         | Bronze            |
| Insulation housing               | Polyamide 6.6     |
| Flammability class UL 94         | V-2               |
| Working temperature, min.        | -40 °C            |
| Working temperature, max.        | 105 °C            |
| Further technical data           |                   |
| Mounting type                    | Plug in           |
| Insulation available             | $\checkmark$      |
| Touch protection is available    | $\checkmark$      |
| Number of bridged terminals      | 8                 |
| Environmental Product Compliance |                   |
| REACH Conform                    | yes               |
| REACH Reference date             | 2023-06-14        |
| REACH Candidate Substance Note   | No                |
| RoHS Conform                     | yes               |
|                                  |                   |

Media






### Accessories

#### Insulation cap for cross-connector

| Insulating cap, | Colour: Yellow |               |                   |
|-----------------|----------------|---------------|-------------------|
| Article number  | Article name   | GTIN (EAN)    | Packaging<br>unit |
| 17200.8         | SQIK 2,5-10 YE | 4044211148539 | 20                |

#### ##INVERSE##CONTA-CONNECT



| Article number | Article name | GTIN (EAN)    | Packaging<br>unit |
|----------------|--------------|---------------|-------------------|
| 17566.2        | SRKD 4/D5 BG | 4044211234669 | 100 ST            |



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name  | GTIN (EAN)    | Packaging<br>unit |
|----------------|---------------|---------------|-------------------|
| 17569.2        | SRKD 4/RD5 BG | 4044211234690 | 100 ST            |



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name | GTIN (EAN)    | Packaging<br>unit |
|----------------|--------------|---------------|-------------------|
| 17563.2        | SRKD 4/D2 BG | 4044211234638 | 100 ST            |



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name | GTIN (EAN)    | Packaging<br>unit |
|----------------|--------------|---------------|-------------------|
| 17564.2        | SRKD 4/D3 BG | 4044211234645 | 100 ST            |



#### ##INVERSE##CONTA-CONNECT



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name | GTIN (EAN)    | Packaging<br>unit |
|----------------|--------------|---------------|-------------------|
| 17565.2        | SRKD 4/D4 BG | 4044211234652 | 100 ST            |



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name              | GTIN (EAN)    | Packaging<br>unit |
|----------------|---------------------------|---------------|-------------------|
| 17570.2        | SRKD 4/LED1(RD)/24V DC BG | 4044211234706 | 100 ST            |



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name              | GTIN (EAN)    | Packaging<br>unit |
|----------------|---------------------------|---------------|-------------------|
| 17571.2        | SRKD 4/LED1(GN)/24V DC BG | 4044211234713 | 100 ST            |



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name              | GTIN (EAN)    | Packaging<br>unit |
|----------------|---------------------------|---------------|-------------------|
| 17572.2        | SRKD 4/LED2(RD)/24V DC BG | 4044211234720 | 100 ST            |



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name              | GTIN (EAN)    | Packaging<br>unit |
|----------------|---------------------------|---------------|-------------------|
| 17575.2        | SRKD 4/LED3(GN)/24V DC BG | 4044211234751 | 100 ST            |



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name              | GTIN (EAN)    | Packaging<br>unit |
|----------------|---------------------------|---------------|-------------------|
| 17576.2        | SRKD 4/LED4(RD)/24V DC BG | 4044211234768 | 100 ST            |



#### ##INVERSE##CONTA-CONNECT



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name              | GTIN (EAN)    | Packaging<br>unit |
|----------------|---------------------------|---------------|-------------------|
| 17578.2        | SRKD 4/LED5(RD)/24V AC BG | 4044211234782 | 100 ST            |




Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name               | GTIN (EAN)    | Packaging<br>unit |
|----------------|----------------------------|---------------|-------------------|
| 17579.2        | SRKD 4/LED5(RD)/230V AC BG | 4044211234799 | 100 ST            |



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name | GTIN (EAN)    | Packaging<br>unit |
|----------------|--------------|---------------|-------------------|
| 17561.2        | SRKD 4/D0 BG | 4044211234614 | 100 ST            |



| Article number | Article name | GTIN (EAN)    | Packaging<br>unit |
|----------------|--------------|---------------|-------------------|
| 17562.2        | SRKD 4/D1 BG | 4044211234621 | 100 ST            |



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name | GTIN (EAN)    | Packaging<br>unit |
|----------------|--------------|---------------|-------------------|
| 17567.2        | SRKD 4/D6 BG | 4044211234676 | 100 ST            |



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name  | GTIN (EAN)    | Packaging<br>unit |
|----------------|---------------|---------------|-------------------|
| 17568.2        | SRKD 4/RD1 BG | 4044211234683 | 100 ST            |



#### ##INVERSE##CONTA-CONNECT



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name              | GTIN (EAN)    | Packaging<br>unit |
|----------------|---------------------------|---------------|-------------------|
| 17573.2        | SRKD 4/LED2(GN)/24V DC BG | 4044211234737 | 100 ST            |



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name              | GTIN (EAN)    | Packaging<br>unit |
|----------------|---------------------------|---------------|-------------------|
| 17574.2        | SRKD 4/LED3(RD)/24V DC BG | 4044211234744 | 100 ST            |



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name              | GTIN (EAN)    | Packaging<br>unit |
|----------------|---------------------------|---------------|-------------------|
| 17577.2        | SRKD 4/LED4(GN)/24V DC BG | 4044211234775 | 100 ST            |



Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Black

| Article number | Article name                  | GTIN (EAN)    | Packaging<br>unit |
|----------------|-------------------------------|---------------|-------------------|
| 17172.4        | SSIK 4/2A/LED 30-60V AC/DC BK | 4044211180447 | 25 ST             |



Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Black

| Article number | Article name | GTIN (EAN)    | Packaging<br>unit |
|----------------|--------------|---------------|-------------------|
| 17150.4        | SSIK 4/2A BK | 4044211179816 | 50 ST             |



Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Black

| Article number | Article name                  | GTIN (EAN)    | Packaging<br>unit |
|----------------|-------------------------------|---------------|-------------------|
| 17171.4        | SSIK 4/2A/LED 12-30V AC/DC BK | 4044211180430 | 25 ST             |



#### ##INVERSE##CONTA-CONNECT



Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Black

| Article number | Article name                    | GTIN (EAN)    | Packaging<br>unit |
|----------------|---------------------------------|---------------|-------------------|
| 17173.4        | SSIK 4/2A/LED 110-250V AC/DC BK | 4044211180454 | 25 ST             |




Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Black

| Article number | Article name                | GTIN (EAN)    | Packaging<br>unit |
|----------------|-----------------------------|---------------|-------------------|
| 17174.4        | SSIK 4/2A/LED 500V AC/DC BK | 4044211180461 | 25 ST             |

Double-level terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

| Article number | Article name | GTIN (EAN)    | Packaging<br>unit |
|----------------|--------------|---------------|-------------------|
| 17185.2        | SRKD 4 BG    | 4044211190712 | 100               |



| Article number | Article name | GTIN (EAN)    | Packaging<br>unit |
|----------------|--------------|---------------|-------------------|
| 17186.2        | SRKD 4/SV BG | 4044211190736 | 100               |



Protective-earth double-level terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Green-yellow

| Article number | Article name | GTIN (EAN)    | Packaging<br>unit |
|----------------|--------------|---------------|-------------------|
| <u>17187.2</u> | SSLD 4 GNYE  | 4044211190750 | 100 ST            |



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6 mm, Colour: Beige

| Article number | Article name  | GTIN (EAN)    | Packaging<br>unit |
|----------------|---------------|---------------|-------------------|
| 17106.2        | SRK 4/2A/Z BG | 4044211141714 | 100 ST            |



#### ##INVERSE##CONTA-CONNECT



Protective earth terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6 mm, Colour: Green-yellow

| Article number | Article name  | GTIN (EAN)    | Packaging<br>unit |
|----------------|---------------|---------------|-------------------|
| 17107.2        | SSL 4/2A GNYE | 4044211141721 | 100 ST            |



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6 mm, Colour: Black-yellow

| Article number | Article name     | GTIN (EAN)    | Packaging<br>unit |
|----------------|------------------|---------------|-------------------|
| 17155.2        | SRK 4/2A/PE BKYE | 4044211186692 | 100 ST            |

Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6 mm, Colour: Beige

| Article number | Article name | GTIN (EAN)    | Packaging<br>unit |
|----------------|--------------|---------------|-------------------|
| 17104.2        | SRK 4/2A BG  | 4044211141691 | 100               |



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6 mm, Colour: Beige

| Article number | Article name  | GTIN (EAN)    | Packaging<br>unit |
|----------------|---------------|---------------|-------------------|
| 17105.2        | SRK B 4/2A BG | 4044211141707 | 100 ST            |