

Insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 60.1 mm, Rated cross-section: 4 mm², Colour: Black

RAL: 9005

Business data

Article number	17219.4
Article name	SQI 4/10 BK
GTIN (EAN)	4044211175528
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	7 g
Weight per piece (including packaging)	7.1 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	17219.8
Product description	Insulated cross-connector



Technical data

Length4 mmWidth60.1 mmHeight23 mmPitch size6 mmRatings1000 VVoltage with partition, max.1000 VVoltage without partition, max.1000 VRated current32 ACurrent load, max.41 ARated cross-section4 mm²Contamination degree2Contamination degree2Contamination degree10MaterialBronzeInsulation housingPolyamide 6.6Flammability class UL 94V-2Working temperature, min40 °CWorking temperature, max.105 °CFurther technical dataVMounting typePlug inInsulation available√Vorking temperature, max.105 °CFurther technical data10Reader of bridged terminals10Environmental Product ComplianceVREACH ConformyesREACH ConformyesReACH Candidate Substance NoteNoRoth S Conformyes	Dimensions	
Height23 mmPitch size6 mmRatings $1000 V$ Voltage with partition, max.1000 VRated current32 ACurrent load, max.41 ARated cross-section4 mm²Contamination degree2Connection data $V = 2$ No. of poles10Materials $Material$ Hisulation housingPolyamide 6.6Flammability class UL 94 $V - 2$ Working temperature, min40 °CWorking temperature, max.105 °CFurther technical data $$ Mounting typePlug inInsulation available $\sqrt{$ Touch protection is available $\sqrt{$ Number of bridged terminals10Environmental Product Compliance $\sqrt{$ REACH ConformyesREACH Reference date2023-06-14REACH Candidate Substance NoteNo	Length	4 mm
Pitch size 6 mm Ratings 1000 V Voltage with partition, max. 1000 V Rated current 32 A Current load, max. 41 A Rated corse-section 4 mm² Contamination degree 2 Connection data 2 No. of poles 10 Materials Bronze Insulation housing Polyamide 6.6 Flammability class UL 94 V-2 Working temperature, min. -40 °C Working temperature, min. -40 °C Working temperature, max. 105 °C Further technical data 10 Mounting type Plug in Insulation available √ Touch protection is available √ Number of bridged terminals 10 Environmental Product Compliance REACH Conform REACH Reference date 2023-06-14 REACH Candidate Substance Note No	Width	60.1 mm
RatingsVoltage with partition, max. $1000 \vee$ Voltage without partition, max. $1000 \vee$ Rated current 32 A Current load, max. 41 A Rated cross-section 4 mm^2 Contamination degree 2 Connection data 10 No. of poles 10 Materials $Material$ MaterialBronzeInsulation housingPolyamide 6.6Flammability class UL 94 $V-2$ Working temperature, min. $-40 \degree C$ Working temperature, max. $105 \degree C$ Further technical data \sqrt Mounting typePlug inInsulation available \checkmark Number of bridged terminals 10 Environmental Product Compliance 10 REACH ConformyesREACH Reference date $2023-06-14$ REACH Candidate Substance NoteNo	Height	23 mm
Voltage with partition, max. $1000 \vee$ Voltage without partition, max. $1000 \vee$ Rated current 32 A Current load, max. 41 A Rated cross-section 4 mm^2 Contamination degree 2 Connection data $No. of poles$ No. of poles 10 MaterialBronzeInsulation housingPolyamide 6.6Flammability class UL 94V-2Working temperature, min40 °CWorking temperature, max. $105 °C$ Further technical data \sqrt Mounting typePlug inInsulation available \checkmark Number of bridged terminals 10 Environmental Product Compliance $REACH Conform$ REACH Reference date $2023-06-14$ REACH Candidate Substance NoteNo	Pitch size	6 mm
Voltage without partition, max.1000 VRated current32 ACurrent load, max.41 ARated cross-section4 mm²Contamination degree2Connection data 10 Materials10MaterialBronzeInsulation housingPolyamide 6.6Flammability class UL 94V-2Working temperature, min40 °CWorking temperature, max.105 °CFurther technical dataMounting typePlug inInsulation available \checkmark Touch protection is available \checkmark Number of bridged terminals10Environmental Product Compliance10REACH ConformyesREACH Reference date2023-06-14REACH Candidate Substance NoteNo	Ratings	
Rated current32 ACurrent load, max.41 ARated cross-section4 mm²Contamination degree2Connection dataNo. of poles10MaterialsMaterialMaterialBronzeInsulation housingPolyamide 6.6Flammability class UL 94V-2Working temperature, min40 °CWorking temperature, max.105 °CFurther technical dataMounting typeMounting typePlug inInsulation available✓Vorker of bridged terminals10Environmental Product Compliance10REACH ConformyesREACH ConformyesREACH Candidate Substance NoteNo	Voltage with partition, max.	1000 V
Current load, max.41 ARated cross-section4 mm²Contamination degree2Connection data 10 No. of poles10MaterialsBronzeInsulation housingPolyamide 6.6Flammability class UL 94V-2Working temperature, min40 °CWorking temperature, max.105 °CFurther technical data \sqrt Mounting typePlug inInsulation available \checkmark Number of bridged terminals10Environmental Product Compliance $\sqrt{23-06-14}$ REACH ConformyesREACH Candidate Substance NoteNo	Voltage without partition, max.	1000 V
Rated cross-section4 mm²Contamination degree2Connection dataNo. of poles10MaterialsMaterialBronzeInsulation housingPolyamide 6.6Flammability class UL 94V-2Working temperature, min40 °CWorking temperature, max.105 °CFurther technical dataMounting typePlug inInsulation available✓Touch protection is available✓Vorking termental Product Compliance10Environmental Product Compliance2023-06-14REACH Candidate Substance NoteNo	Rated current	32 A
Contamination degree2Connection dataNo. of poles10MaterialsMaterialBronzeInsulation housingPolyamide 6.6Flammability class UL 94V-2Working temperature, min40 °CWorking temperature, max.105 °CFurther technical dataMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals10Environmental Product Compliance10REACH ConformyesREACH Reference date2023-06-14REACH Candidate Substance NoteNo	Current load, max.	41 A
Connection data No. of poles 10 Materials Bronze Insulation housing Polyamide 6.6 Flammability class UL 94 V-2 Working temperature, min. -40 °C Working temperature, max. 105 °C Further technical data Mounting type Mounting type Plug in Insulation available ✓ Touch protection is available ✓ Number of bridged terminals 10 Environmental Product Compliance REACH Conform REACH Reference date 2023-06-14 REACH Candidate Substance Note No	Rated cross-section	4 mm ²
No. of poles10MaterialsBronzeInsulation housingPolyamide 6.6Flammability class UL 94V-2Working temperature, min40 °CWorking temperature, max.105 °CFurther technical dataMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals10Environmental Product ComplianceREACH ConformyesREACH Reference date2023-06-14REACH Candidate Substance NoteNo	Contamination degree	2
Material Bronze Insulation housing Polyamide 6.6 Flammability class UL 94 V-2 Working temperature, min. -40 °C Working temperature, max. 105 °C Further technical data Mounting type Mounting type Plug in Insulation available ✓ Touch protection is available ✓ Number of bridged terminals 10 Environmental Product Compliance REACH Conform REACH Reference date 2023-06-14 REACH Candidate Substance Note No	Connection data	
MaterialBronzeInsulation housingPolyamide 6.6Flammability class UL 94V-2Working temperature, min40 °CWorking temperature, max.105 °CFurther technical dataMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals10Environmental Product Compliance10REACH ConformyesREACH Reference date2023-06-14REACH Candidate Substance NoteNo	No. of poles	10
Insulation housingPolyamide 6.6Flammability class UL 94V-2Working temperature, min40 °CWorking temperature, max.105 °CFurther technical dataMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals10Environmental Product ComplianceyesREACH ConformyesREACH Reference date2023-06-14REACH Candidate Substance NoteNo	Materials	
Flammability class UL 94V-2Working temperature, min40 °CWorking temperature, max.105 °CFurther technical dataMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals10Environmental Product ComplianceREACH ConformyesREACH Reference date2023-06-14REACH Candidate Substance NoteNo	Material	Bronze
Working temperature, min40 °CWorking temperature, max.105 °CFurther technical dataMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals10Environmental Product ComplianceREACH ConformyesREACH Reference date2023-06-14REACH Candidate Substance NoteNo	Insulation housing	Polyamide 6.6
Working temperature, max.105 °CFurther technical dataPlug inMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals10Environmental Product ComplianceREACH ConformyesREACH Reference date2023-06-14REACH Candidate Substance NoteNo	Flammability class UL 94	V-2
Further technical data Mounting type Plug in Insulation available ✓ Touch protection is available ✓ Number of bridged terminals 10 Environmental Product Compliance yes REACH Conform yes REACH Reference date 2023-06-14 REACH Candidate Substance Note No	Working temperature, min.	-40 °C
Mounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals10Environmental Product ComplianceREACH ConformyesREACH Reference date2023-06-14REACH Candidate Substance NoteNo	Working temperature, max.	105 °C
Insulation available✓Touch protection is available✓Number of bridged terminals10Environmental Product ComplianceREACH ConformyesREACH Reference date2023-06-14REACH Candidate Substance NoteNo	Further technical data	
Touch protection is available✓Number of bridged terminals10Environmental Product ComplianceREACH ConformyesREACH Reference date2023-06-14REACH Candidate Substance NoteNo	Mounting type	Plug in
Number of bridged terminals10Environmental Product ComplianceREACH ConformyesREACH Reference date2023-06-14REACH Candidate Substance NoteNo	Insulation available	\checkmark
Environmental Product Compliance REACH Conform yes REACH Reference date 2023-06-14 REACH Candidate Substance Note No	Touch protection is available	\checkmark
REACH ConformyesREACH Reference date2023-06-14REACH Candidate Substance NoteNo	Number of bridged terminals	10
REACH Reference date 2023-06-14 REACH Candidate Substance Note No	Environmental Product Compliance	
REACH Candidate Substance Note No	REACH Conform	yes
	REACH Reference date	2023-06-14
RoHS Conform yes	REACH Candidate Substance Note	No
	RoHS Conform	yes

Media






Accessories

Insulation cap for cross-connector

Insulating cap,	Colour: Yellow		
Article number	Article name	GTIN (EAN)	Packaging unit
17200.8	SQIK 2,5-10 YE	4044211148539	20

##INVERSE##CONTA-CONNECT



Article number	Article name	GTIN (EAN)	Packaging unit
<u>17566.2</u>	SRKD 4/D5 BG	4044211234669	100 ST



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17569.2	SRKD 4/RD5 BG	4044211234690	100 ST



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17563.2	SRKD 4/D2 BG	4044211234638	100 ST



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17564.2	SRKD 4/D3 BG	4044211234645	100 ST



##INVERSE##CONTA-CONNECT



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17565.2	SRKD 4/D4 BG	4044211234652	100 ST



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17570.2	SRKD 4/LED1(RD)/24V DC BG	4044211234706	100 ST



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17571.2	SRKD 4/LED1(GN)/24V DC BG	4044211234713	100 ST



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17572.2	SRKD 4/LED2(RD)/24V DC BG	4044211234720	100 ST



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17575.2	SRKD 4/LED3(GN)/24V DC BG	4044211234751	100 ST



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17576.2	SRKD 4/LED4(RD)/24V DC BG	4044211234768	100 ST



##INVERSE##CONTA-CONNECT



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17578.2	SRKD 4/LED5(RD)/24V AC BG	4044211234782	100 ST




Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17579.2	SRKD 4/LED5(RD)/230V AC BG	4044211234799	100 ST

Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17561.2	SRKD 4/D0 BG	4044211234614	100 ST



Article number	Article name	GTIN (EAN)	Packaging unit
17562.2	SRKD 4/D1 BG	4044211234621	100 ST



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17567.2	SRKD 4/D6 BG	4044211234676	100 ST



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17568.2	SRKD 4/RD1 BG	4044211234683	100 ST



##INVERSE##CONTA-CONNECT



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17573.2	SRKD 4/LED2(GN)/24V DC BG	4044211234737	100 ST



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17574.2	SRKD 4/LED3(RD)/24V DC BG	4044211234744	100 ST



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17577.2	SRKD 4/LED4(GN)/24V DC BG	4044211234775	100 ST



Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
17172.4	SSIK 4/2A/LED 30-60V AC/DC BK	4044211180447	25 ST



Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
17150.4	SSIK 4/2A BK	4044211179816	50 ST



Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
17171.4	SSIK 4/2A/LED 12-30V AC/DC BK	4044211180430	25 ST



##INVERSE##CONTA-CONNECT



Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
17173.4	SSIK 4/2A/LED 110-250V AC/DC BK	4044211180454	25 ST




Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
17174.4	SSIK 4/2A/LED 500V AC/DC BK	4044211180461	25 ST

Double-level terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17185.2	SRKD 4 BG	4044211190712	100



Article number	Article name	GTIN (EAN)	Packaging unit
17186.2	SRKD 4/SV BG	4044211190736	100



Protective-earth double-level terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
<u>17187.2</u>	SSLD 4 GNYE	4044211190750	100 ST



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17106.2	SRK 4/2A/Z BG	4044211141714	100 ST



##INVERSE##CONTA-CONNECT



Protective earth terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
17107.2	SSL 4/2A GNYE	4044211141721	100 ST



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6 mm, Colour: Black-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
17155.2	SRK 4/2A/PE BKYE	4044211186692	100 ST



Article number	Article name	GTIN (EAN)	Packaging unit
17104.2	SRK 4/2A BG	4044211141691	100



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17105.2	SRK B 4/2A BG	4044211141707	100 ST