Data sheet 2764.2 AQI 3/50 YE





External insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 57.04 mm, Rated current: 150 A; Colour: Yellow

RAL: 1026

Business data

Dusiness data	
Article number	2764.2
Article name	AQI 3/50 YE
GTIN (EAN)	4044211054946
Packaging unit	5
Quantity unit	PC
Weight per piece (not including packaging)	55.8 g
Weight per piece (including packaging)	56.9 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	2764.2
Product description	External insulated cross-connector

Data sheet





Technical data		
Dimensions		
Width	57.04 mm	
Pitch size	20 mm	
Ratings		
Voltage with partition, max.	1000 V	
Voltage without partition, max.	1000 V	
Rated current	150 A	
Contamination degree	3	
Connection data		
No. of poles	3	
Materials		
Material	Copper	
Surface	Tin-plated	
Insulation housing	Polyamide 6.6	
Flammability class UL 94	V-2	
Working temperature, min.	-40 °C	
Working temperature, max.	105 °C	
Further technical data		
Mounting type	Plug in	
Insulation available	✓	
Touch protection is available	✓	
Number of bridged terminals	3	
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2023-06-14	
REACH Candidate Substance Note	No	
RoHS Conform	yes	

Data sheet 2764.2 AQI 3/50 YE



Media

Data sheet

2764.2 AQI 3/50 YE



Accessories

##INVERSE##CONTA-CONNECT



Feed-through terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 240 mm², Width: 36 mm, Colour: Black-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
1570.2	RK 240/PE BKYE	4044211047412	5 ST



Feed-through terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 95 mm², Width: 25 mm, Colour: Black-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1568.2</u>	RK 95/PE BKYE	4044211047399	10 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 50 mm², Width: 20 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1582.2</u>	RK 50-D BG	4044211047702	10



Feed-through terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 50 mm², Width: 20 mm, Colour: Black-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1567.2</u>	RK 50/PE BKYE	4044211047382	10 ST



Feed-through terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 150 mm², Width: 31 mm, Colour: Black-yellow

Artic	cle number	Article name	GTIN (EAN)	Packaging unit
1569	0.2	RK 150/PE BKYE	4044211047405	5 ST



Feed-through terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 50 mm², Width: 20 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1120.2	RK 50 BG	4044211018702	10

Data sheet 2764.2 AQI 3/50 YE



##INVERSE##CONTA-CONNECT



Ex feed-through terminal ATEX-certified, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 50 mm², Width: 20 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1473.2	RK 50 Ex BG	4044211107901	10