Data sheet

2938.0 SI 5x20 5,000A-F

Fuse, Dimensions: 5x20 mm, Trigger characteristic: Fast-acting (F); Rated voltage: 250 V, Rated current: 5 A

Business data

Article number	2938.0
Article name	SI 5x20 5,000A-F
GTIN (EAN)	4044211056636
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	0.86 g
Weight per piece (including packaging)	0.9 g
Unit of weight	G
Customs number	85361010
Country of origin	DE
Product description	fuse

Data sheet

2938.0 SI 5x20 5,000A-F

Technical data

Dimensions	
Length	20 mm
Diameter of contact cap	5.2 mm
Dimensions	5x20 mm
Ratings	
Rated voltage	250 V
Rated current	5 A
Materials	
Contact caps	Brass
Surface	Nickel
Tube	Glass
Further technical data	
Trigger characteristic	Fast-acting (F)
Rated breaking capacity	50 A @ AC 250 V
Voltage drop	100 mV
Power loss (@ 1.5 In)	1.7 W
Melting integral I^2ts	42 A^2s
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Approvals

Standards and regulations

Standards / specifications	IEC 60127-2/2 EN 60127-2/2 VDE 0820-2/2

Data sheet

2938.0 SI 5x20 5,000A-F

Media

Accessories