



Insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 58.9 mm, Rated cross-section: 4 mm<sup>2</sup>, Colour: Yellow

### **RAL:** 1026

### **Business data**

Article number	<u>3728.8</u>
Article name	ZQI 4/10 YE
GTIN (EAN)	4044211060466
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	7.28 g
Weight per piece (including packaging)	7.48 g
Unit of weight	G
Customs number	85389099
Country of origin	CZ
Prio-Article	3728.8
Product description	Insulated cross-connector

# Data sheet 3728.8 ZQI 4/10 YE



### **Technical data**

Dimensions	
Length	4.5 mm
Width	58.9 mm
Pitch size	6 mm
Ratings	
Voltage with partition, max.	800 V
Voltage without partition, max.	800 V
Rated current	32 A
Rated cross-section	4 mm <sup>2</sup>
Contamination degree	3
Connection data	
No. of poles	10
Materials	
Material	Copper alloy
Surface	Tin-plated
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C
Further technical data	
Mounting type	Plug in
Insulation available	$\checkmark$
Touch protection is available	$\checkmark$
Number of bridged terminals	10
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

# Data sheet 3728.8 ZQI 4/10 YE

Media



# Data sheet 3728.8 ZQI 4/10 YE

**ZCONTACLIP** 

Accessories



#### ##INVERSE##CONTA-CONNECT

Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3515.2</u>	ZRK 4/2A BG	4044211151751	100

Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1716.2</u>	ZRK 4/2A Ex BG	4044211058579	100

Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

	5 35/7.5, Rated cross-section: 4 mm²,	width: 6.1 mm, Colour	Beige
Article number	Article name	GTIN (EAN)	Packaging unit
<u>1717.2</u>	ZRK 4/3A Ex BG	4044211058609	100

Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3516.2	ZRK 4/3A BG	4044211151775	100

Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

DIA	Article number	Article name	GTIN (EAN)	Packaging unit
	<u>1718.2</u>	ZRK 4/4A Ex BG	4044211058630	100

Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
 3517.2	ZRK 4/4A BG	4044211151782	100