Data sheet

4950.0 SI 6,3x32 0,100A-T

Fuse, Dimensions: 6.3x32 mm, Trigger characteristic: Slow-acting (T); Rated voltage: 500 / 440 / 250 V, Rated current: 0.1 A

Business data

Article number	4950.0
Article name	SI 6,3x32 0,100A-T
GTIN (EAN)	4044211109127
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	2.66 g
Weight per piece (including packaging)	2.7 g
Unit of weight	G
Customs number	85361010
Country of origin	EU
Product description	fuse

Data sheet

4950.0 SI 6,3x32 0,100A-T

Technical data

Dimensions	
Length	31.8 mm
Diameter of contact cap	6.35 mm
Dimensions	6,3x32 mm
Ratings	
Rated voltage	500 / 440 / 250 V
Rated current	0.1 A
Materials	
Contact caps	Brass
Surface	Nickel
Tube	Ceramic
Further technical data	
Trigger characteristic	Time-lag (T)
Rated breaking capacity	1,5 kA @ AC 500 (cosφ = 1 10 kA @ AC 440 V cosφ = 0,3)
Voltage drop	3600 mV
Power loss (@ 1.5 In)	1.3 W
Melting integral I^2ts	0.04 A^2s
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet

4950.0 SI 6,3x32 0,100A-T

Media

Accessories