# Data sheet

## 4973.0 SI 6,3x32 0,250A-F

Fuse, Dimensions: 6.3x32 mm, Trigger characteristic: Fast-acting (F); Rated voltage: 500 / 440 V, Rated current: 0.25 A

### Business data

| | |
|---|---|
| Article number | 4973.0 |
| Article name | SI 6,3x32 0,250A-F |
| GTIN (EAN) | 4044211109356 |
| Packaging unit | 10 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 0.96 g |
| Weight per piece (including packaging) | 1 g |
| Unit of weight | G |
| Customs number | 85361010 |
| Country of origin | EU |
| Product description | fuse |

# Data sheet

## 4973.0 SI 6,3x32 0,250A-F

## Technical data

| | |
|---|---|
| **Dimensions** | |
| Length | 31.8 mm |
| Diameter of contact cap | 6.35 mm |
| Dimensions | 6,3x32 mm |
| **Ratings** | |
| Rated voltage | 500 / 440 V |
| Rated current | 0.25 A |
| **Materials** | |
| Contact caps | Brass |
| Surface | Nickel |
| Tube | Ceramic |
| **Further technical data** | |
| Trigger characteristic | Fast-acting (F) |
| Rated breaking capacity | 50 kA @ AC 500 (cosφ = 0,3) |
| Voltage drop | 6000 mV |
| Power loss (@ 1.5 In) | 3.4 W |
| Melting integral $I^2ts$ | 0.0085 $A^2s$ |
| **Environmental Product Compliance** | |
| REACH Conform | yes |
| REACH Reference date | 2023-06-14 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

# Data sheet

## 4973.0 SI 6,3x32 0,250A-F

### Media

# Data sheet

## 4973.0 SI 6,3x32 0,250A-F

## Accessories