



Fuse, Dimensions: 6.3x32 mm, Trigger characteristic: Fast-acting (F); Rated voltage: 500 / 440 V, Rated current: 1 A

**Business data**

|                                            |                    |
|--------------------------------------------|--------------------|
| Article number                             | 4979.0             |
| Article name                               | SI 6,3x32 1,000A-F |
| GTIN (EAN)                                 | 4044211109417      |
| Packaging unit                             | 10                 |
| Quantity unit                              | PC                 |
| Weight per piece (not including packaging) | 0.96 g             |
| Weight per piece (including packaging)     | 1 g                |
| Unit of weight                             | G                  |
| Customs number                             | 85361010           |
| Country of origin                          | EU                 |
| Product description                        | fuse               |

### Technical data

#### Dimensions

|                         |           |
|-------------------------|-----------|
| Length                  | 31.8 mm   |
| Diameter of contact cap | 6.35 mm   |
| Dimensions              | 6,3x32 mm |

#### Ratings

|               |             |
|---------------|-------------|
| Rated voltage | 500 / 440 V |
| Rated current | 1 A         |

#### Materials

|              |         |
|--------------|---------|
| Contact caps | Brass   |
| Surface      | Nickel  |
| Tube         | Ceramic |

#### Further technical data

|                                                |                                        |
|------------------------------------------------|----------------------------------------|
| Trigger characteristic                         | Fast-acting (F)                        |
| Rated breaking capacity                        | 50 kA @ AC 500 ( $\cos\varphi = 0,3$ ) |
| Voltage drop                                   | 400 mV                                 |
| Power loss (@ 1.5 I <sub>n</sub> )             | 1.2 W                                  |
| Melting integral I <sup>2</sup> t <sub>s</sub> | 0.4 A <sup>2</sup> s                   |

#### Environmental Product Compliance

|                                |            |
|--------------------------------|------------|
| REACH Conform                  | yes        |
| REACH Reference date           | 2023-06-14 |
| REACH Candidate Substance Note | No         |
| RoHS Conform                   | yes        |

---

Media

---

---

Accessories

---