Data sheet







Fuse, Dimensions: 6.3x32 mm, Trigger characteristic: Fast-acting (F); Rated voltage: 500 / 440 V, Rated current: 3.15 A

Business data

Article number	<u>4984.0</u>
Article name	SI 6,3x32 3,150A-F
GTIN (EAN)	4044211109462
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	0.96 g
Weight per piece (including packaging)	1 g
Unit of weight	G
Customs number	85361010
Country of origin	EU
Product description	fuse

Data sheet



4984.0 SI 6,3x32 3,150A-F

Tackwinel date	
Technical data	
Dimensions	
Length	31.8 mm
Diameter of contact cap	6.35 mm
Dimensions	6,3x32 mm
Ratings	
Rated voltage	500 / 440 V
Rated current	3.15 A
Materials	
Contact caps	Brass
Surface	Nickel
Tube	Ceramic
Further technical data	
Trigger characteristic	Fast-acting (F)
Rated breaking capacity	50 kA @ AC 500 (cosφ = 0,3)
Voltage drop	240 mV
Power loss (@ 1.5 ln)	2.3 W
Melting integral I2ts	9 A²s
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet



4984.0 SI 6,3x32 3,150A-F

Media

Data sheet 4984.0 SI 6,3x32 3,150A-F



Accessories