



Fuse, Dimensions: 6.3x32 mm, Trigger characteristic: Fast-acting (F); Rated voltage: 500 / 440 V, Rated current: 4 A

Business data

Article number	4985.0
Article name	SI 6,3x32 4,000A-F
GTIN (EAN)	4044211109479
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	2.66 g
Weight per piece (including packaging)	2.7 g
Unit of weight	G
Customs number	85361010
Country of origin	EU
Product description	fuse

Technical data

Dimensions

Length	31.8 mm
Diameter of contact cap	6.35 mm
Dimensions	6,3x32 mm

Ratings

Rated voltage	500 / 440 V
Rated current	4 A

Materials

Contact caps	Brass
Surface	Nickel
Tube	Ceramic

Further technical data

Trigger characteristic	Fast-acting (F)
Rated breaking capacity	50 kA @ AC 500 ($\cos\varphi = 0,3$)
Voltage drop	220 mV
Power loss (@ 1.5 I _n)	2.6 W
Melting integral I ² t _s	18 A ² s

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Media

Accessories
