



Fuse, Dimensions: 6.3x32 mm, Trigger characteristic: Fast-acting (F); Rated voltage: 500 / 440 V, Rated current: 8 A

Business data

| Article number | 4988.0 |
|--|--------------------|
| Article name | SI 6,3x32 8,000A-F |
| GTIN (EAN) | 4044211109509 |
| Packaging unit | 10 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 0.96 g |
| Weight per piece (including packaging) | 1 g |
| Unit of weight | G |
| Customs number | 85361010 |
| Country of origin | EU |
| Product description | fuse |



Technical data

| Dimensions | |
|------------------------------------|----------------------------|
| Length | 31.8 mm |
| Diameter of contact cap | 6.35 mm |
| Dimensions | 6,3x32 mm |
| Ratings | |
| Rated voltage | 500 / 440 V |
| Rated current | 8 A |
| Materials | |
| Contact caps | Brass |
| Surface | Nickel |
| Tube | Ceramic |
| Further technical data | |
| Trigger characteristic | Fast-acting (F) |
| Rated breaking capacity | 1,5 kA @ AC 500 (cosφ = 1) |
| Voltage drop | 160 mV |
| Power loss (@ 1.5 ln) | 3.7 W |
| Melting integral I ² ts | 150 A²s |
| Environmental Product Compliance | |
| REACH Conform | yes |
| REACH Reference date | 2023-06-14 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |
| | |

Media



Accessories